



14700 Downey Avenue
P.O. Box 1418
Paramount, CA 90723-1418
(562) 531-2060

PRODUCT SPECIFICATIONS

PRODUCT: EMULSIFIED ASPHALT

GRADE: PMCRS-2h

PRODUCT CODE: 13602

DESCRIPTION: A polymer modified cationic rapid setting emulsion manufactured from hard base asphalt.

MEETS SPECIFICATIONS: State of California

TESTS	ASTM METHOD	ASHTO METHOD	SPECS.	TYPICAL ANALYSIS ¹
Viscosity, Saybolt, 122°F, SFS	D244	T59	75-300	134
Storage, Stability, 24 H, %	D244	T59	1 max	0.01
Ph	E70	T200	6.7 max	3.3
Particle Charge Test	D244	E70	positive	pos.
Classification Test	D244	T59	passes	passes
Demulsibility, 35 ml CaCl ₂ , %	D244	T59	40 min	76
Sieve Test, %	D244	T59	0.3 max	0.07
Density, 60°F, lbs/gallon	D244	T59		8.40
Ash content, %	D3723		0.2 max	0.1
Residue by evaporation, %	D244	T59	65 min	70
Tests on residue from evaporation:				
Penetration, 77°F, 100g, 5s	D5	T49	40-90	51
Abs. Viscosity, 140°F, Poise	D2171	T202		2450
Ductility, 77°F, 5 cm/min, cm	D113	T51	40 min	150+
Torsional recovery, %	Cal332		18 min	19

¹Values shown as typicals may, at times, be superseded by results which are current at a particular time.

AVAILABILITY: Readily available, Elk Grove terminal

DOT SHIPPING NAME: Asphalt, non-hazardous

DOT PLACARD: None required

RELEASED: 02-01-2003