



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

**PRODUCT SPECIFICATIONS**

**PRODUCT:** SATURANT

**GRADE:** 708 **PRODUCT CODE:** 12108

**DESCRIPTION:** A vacuum steam refined straight run asphalt for use as a felt saturant, or as a base asphalt for other roofing products.

**MEETS SPECIFICATIONS:** Paramount Petroleum

<b>TESTS</b>	<b>ASTM METHOD</b>	<b>AASHTO METHOD</b>	<b>SPECS.</b>	<b>TYPICAL ANALYSIS<sup>1</sup></b>
Penetration, 77°F, 100g, 5s	D5	T49	150-180	165
Abs. Viscosity, 140°F, Poise	D2171	T202		510
Flash Point, C.O.C., °F	D92	T48	500 min	545
API Gravity, 60°F	D70	T228		7.8
Density, 60°F, lbs/gallon	D70	T228		8.46
Softening Point, °F	D36	T53		103

<sup>1</sup>Values shown as typicals may, at times, be superseded by results which are current at a particular time.

**AVAILABILITY:** Readily available

**DOT SHIPPING NAME:** UN3257, Elevated temperature liquid, n.o.s., 9, III

**DOT PLACARD:** Hot, 3257

**RELEASED:** 02-01-2004