



14700 Downey Avenue
P.O. Box 1418
Paramount, CA 90723-1418
(562) 531-2060

PRODUCT SPECIFICATIONS

PRODUCT: ROOFING FLUX

GRADE: ORIENTE **PRODUCT CODE:** 12220

DESCRIPTION: A steam refined straight run asphalt flux made from Oriente crude and used in the manufacturing of roofing asphalt.

MEETS SPECIFICATIONS: Paramount Petroleum

TESTS	ASTM METHOD	AASHTO METHOD	SPECS.	TYPICAL ANALYSIS ¹
Viscosity, Kinematic, 275°F, cSt	D2170	T201	240-290	265
Viscosity, Absolute, 140°F, Poise	D2171	T202	700-1100	1023
Flash Point, C.O.C., °F	D92	T48	540 min	550
Penetration, 77°F, dmm	D5	T49		105
Softening Point, °F	D36	T53	80 min	110
API Gravity, 60°F	D70	T228		7.5
Density, 60°F, lbs/Gallon	D70	T228		8.48

¹Values shown as typicals may, at times, be superseded by results which are current at a particular time.

AVAILABILITY: Readily available

DOT SHIPPING NAME: UN3257, Elevated temperature liquid, n.o.s., 9, III

DOT PLACARD: Hot, 3257

RELEASED: 01-01-2007