



14700 Downey Avenue
P.O. Box 1418
Paramount, CA 90723-1418
(562) 531-2060

PRODUCT SPECIFICATIONS

PRODUCT: RECYCLING AGENT

GRADE: RA 25 **PRODUCT CODE:** 13820

DESCRIPTION: A vacuum steam refined straight run asphalt product for use in hot mix recycling for restoring the properties of recycled asphalt pavements.

MEETS SPECIFICATIONS: ASTM D4552

TESTS	ASTM METHOD	AASHTO METHOD	SPECS.	TYPICAL ANALYSIS¹
Viscosity, 140°F, cSt	D2170	T201	901-4500	4000
Flash Point, COC, °F	D92	T48	425 min	555
Saturates, wt. %	D2007		30 max	21.5
Tests on RTFO Residue:	D2872	T240		
Viscosity Ratio, 140°F	D2170	T201	3 max	2.2
Loss on Heating, wt. %	D2872	T240	3 max	1.5
Specific Gravity, 60/60 °F	D70	T228		0.9930
API Gravity, 60°F	D70	T228		11.0
Density, 60°F, Lbs/Gallon	D70	T228		8.27

¹Values shown as typicals may, at times, be superseded by results which are current at a particular time.

AVAILABILITY: Special order only.

DOT SHIPPING NAME: UN3257, Elevated temperature liquid, n.o.s., 9, III

DOT PLACARD: Hot, 3257

RELEASED: 02-01-2003