



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

**PRODUCT SPECIFICATIONS**

**PRODUCT:** RECYCLING AGENT

**GRADE:** RA 25 **PRODUCT CODE:** 13820

**DESCRIPTION:** A vacuum steam refined straight run asphalt product for use in hot mix recycling for restoring the properties of recycled asphalt pavements.

**MEETS SPECIFICATIONS:** ASTM D4552

<b>TESTS</b>	<b>ASTM METHOD</b>	<b>AASHTO METHOD</b>	<b>SPECS.</b>	<b>TYPICAL ANALYSIS<sup>1</sup></b>
Viscosity, 140°F, cSt	D2170	T201	901-4500	4000
Flash Point, COC, °F	D92	T48	425 min	555
Saturates, wt. %	D2007		30 max	21.5
Tests on RTFO Residue:	D2872	T240		
Viscosity Ratio, 140°F	D2170	T201	3 max	2.2
Loss on Heating, wt. %	D2872	T240	3 max	1.5
Specific Gravity, 60/60 °F	D70	T228		0.9930
API Gravity, 60°F	D70	T228		11.0
Density, 60°F, Lbs/Gallon	D70	T228		8.27

<sup>1</sup>Values shown as typicals may, at times, be superseded by results which are current at a particular time.

**AVAILABILITY:** Special order only.

**DOT SHIPPING NAME:** UN3257, Elevated temperature liquid, n.o.s., 9, III

**DOT PLACARD:** Hot, 3257

**RELEASED:** 02-01-2003