



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

## PRODUCT SPECIFICATIONS

**PRODUCT:** RECYCLING AGENT

**GRADE:** RA 75 **PRODUCT CODE:** 13821

**DESCRIPTION:** A vacuum steam refined straight run asphalt product for use in hot mix recycling for restoring the properties of recycled asphalt pavements.

**MEETS SPECIFICATIONS:** ASTM D4552

TESTS	ASTM METHOD	AASHTO METHOD	SPECS.	TYPICAL ANALYSIS <sup>1</sup>
Viscosity, 140°F, cSt	D2170	T201	4501-12000	5000
Flash Point, COC, °F	D92	T48	425 min	560
Saturates, wt. %	D2007		30 max	21.0
Tests on RTFO Residue:	D2872	T240		
Viscosity Ratio, 140°F	D2170	T201	3 max	2.2
Loss on Heating, wt. %	D2872	T240	3 max	1.5
Specific Gravity, 60/60 °F	D70	T228		0.9902
API Gravity, 60°F	D70	T228		10.4
Density, 60°F, Lbs/Gallon	D70	T228		8.31

<sup>1</sup>Values shown as typical may, at times, be superseded by results which are current at a particular time.

**AVAILABILITY:** Readily available

**DOT SHIPPING NAME:** UN3257, Elevated temperature, liquid, n.o.s, 9, III

**DOT PLACARD:** Hot, 3257

**RELEASED:** 02-01-2003